

Model		Heating capacity	Heat distribution	LED illumination	Low Glare	Type of protection	Remote control	Dimensions	
Pedestal radiant heaters Infrared radiant heaters of the IRS-E series									
		IRS 800 E	800 W 2 stages	Warmth to one side	—	—	—	Height: 43.9 cm	
		IRS 1200 E	1,200 W 1 stage	360° all-round warmth	—	-80% less light	IP55 rain-proof	Height: 65 cm	
		IRS 1500 E	1,500 W 1 stage	360° all-round warmth	LED light	-80% less light	IP55 rain-proof	Height: 110 cm	
		IRS 2000 E	2,000 W 3 stages	Warmth to one side	—	-80% less light	IP34	Height: 100 cm	
		IRS 2010 E	2,000 W 2 stages	Warmth to one side	—	-80% less light	IP44	Height: 106.5 cm	
		IRS 2050 E	2,000 W 9 stages	45° oscillation	—	—	IP25 rain-proof	Height: 100 cm	
Pedestal radiant heaters Infrared radiant heaters of the IRS series									
		IRS 2005	2,000 W 3 stages	360° all-round warmth	—	—	IP34	Height: 210 cm	
		IRS 2010	2,000 W 2 stages	Warmth to two sides	LED light	—	IP55 rain-proof	Adjustable in height from 180 cm to 220 cm	
		IRS 2020	2,000 W 2 stages	360° all-round warmth	—	—	IP34	Adjustable in height from 194 cm to 209 cm	
		IRS 2110	2,100 W 3 stages	360° all-round warmth	LED light	—	IP45 rain-proof	Adjustable in height from 190 cm to 220 cm	
		IRS 2520	2,500 W 2 stages	360° all-round warmth	—	—	IP34	Height: 188 cm	
		IRS 3020	3,000 W 2 stages	360° all-round warmth	—	—	IP34	Height: 190 cm	